


**DEVICE FOR OPERATING DISCHARGE LAMPS
BY MEANS OF A TRANSFORMER WITH FOUR
WINDINGS, AND A CORRESPONDING METHOD**

5

Field of the invention

The present invention relates to a device for
10 at least two discharge lamps. Moreover,
invention relates to a corresponding
operating two discharge lamps. In part
present invention relates to electronic
which such a device is integrated. Operating
15 lamps comprises in this case both their starting and
their being alight.



Background of the invention

20 It is known to operate two discharge lamps with two
load circuits. In this case, the term load circuit
refers to the load of a bridge that is used as an
inverter to operate a discharge lamp. Each load circuit
has a dedicated preheating arrangement for the
25 respective lamp. Furthermore, according to the internal
prior art, it is possible to operate two lamps in one
load circuit. Here, the primary coil of a heating
transformer of a series circuit of two lamps is
connected in parallel and the secondary coil of the
30 heating transformer is connected between the two lamps.
Furthermore, it is possible to heat all the filaments
of the lamps by transformer via secondary windings, the
primary winding being situated in a section of the
bridge suitable for the application.

35

It is relatively complicated to implement the load
circuits in terms of circuitry, since electronic
control circuits with relay or transistor switches are
required for a defined, sequential starting and

subsequent joint operation of the lamps. By contrast, relatively favorable control circuits that use only passive components for controlling the preheating exist for the purpose of operating individual lamps. The
5 essential constituent of such circuits is a heat-sensitive resistor with a positive temperature coefficient.

A bridge circuit with a relevant load circuit is
10 illustrated in figure 1. The bridge is implemented for the purpose of inversion as a half bridge with two switching elements 1 and 2 and two capacitors 3 and 4. The load circuit 5 in the bridge comprises a coil 6 in series with a lamp 7 which is connected in parallel
15 both with a resonance capacitor 8 and with a heat-sensitive resistor 9.

The mode of operation of the circuit illustrated in figure 1 may be explained as follows. By actuating the
20 switches 1 and 2 suitably, an AC voltage for the load circuit 5 is generated in the center tap of the bridge from the DC voltage. The frequency of the AC voltage is advantageously in the region of the resonant frequency of the coil 6 and the capacitor 8 for the ignition
25 process of the lamp. Before the ignition, as (PTC) thermistor the resistor 9 with a positive temperature coefficient (PTC) detunes the series resonant circuit 6, 8 in such a way that the required ignition voltage across the lamp 7 or the capacitor 8 is not reached.
30 However, the current is already flowing through the incandescent filaments 10 and 11 of the lamp 7 such that they are preheated for the ignition process. In the meantime, current is likewise flowing through the PTC thermistor 9, which it heats in this preheating
35 phase. Its resistance rises in the process, and so the detuning of the series resonant circuit, 6, 8 is correspondingly reduced such that the ignition voltage

across the lamp 7 can be reached. The PTC thermistor 9 is designed in this case such that it carries a sufficient quantity of current even after ignition in order to remain highly resistant so that the resonance
5 can be maintained at an appropriate level of quality.

For the sake of clarity, the load circuit 5 is illustrated in figure 2a without the coil 6. Figure 2b shows a variant of the load circuit of figure 2a.
10 Connected in series with the PTC thermistor 9 is a series capacitor 12 which has the effect that the detuning of the resonant circuit by the PTC thermistor 9 is not so marked as in the case of the circuit of figure 2a. This means that in this case the ignition
15 voltage is reached more quickly and the lamp is ignited more rapidly as a consequence thereof.

A further variant of the load circuits that are illustrated in figures 2a and 2b is reproduced in 2c.
20 In this case, the series capacitor 12 is chiefly active in the cold state of the PTC thermistor 9, whereas the series circuit of the two capacitors 8 and 9 is only active in the warm state of the PTC thermistor 9, that is to say during the operation and ignition of the
25 lamp.

Summary of the invention

The object of the present invention consists in
30 proposing a cost-effective preheating circuit for operating two lamps.

According to the invention, this object is achieved by means of a device for operating at least one first and
35 one second discharge lamp having a coupling-out device for coupling out a heating current for the incandescent filaments of the discharge lamps from a supply branch

of the device, the coupling-out device having a current control device for controlling the heating current, and a heating transformer unit, and respectively having a first contact device connected to the supply branch, and a second contact device for making contact with the first and second discharge lamp, a secondary coil unit of the heating transformer unit being connected to the first and second contact device for the purpose of supplying the incandescent filaments with heating current.

The advantage of the inventive circuit resides in that by contrast with the preheating circuit for one lamp the additional outlay for preheating a second lamp lies essentially in one component, specifically a transformer for transmitting the heating energy to the incandescent filaments of the two lamps.

The secondary coil unit preferably comprises three coils, specifically a first secondary coil for supplying a first incandescent filament of the first discharge lamp, a second secondary coil for supplying a second incandescent filament of the first discharge lamp and a first incandescent filament of the second discharge lamp, and a third secondary coil for supplying a second incandescent filament of the second discharge lamp. It is thereby possible for the individual incandescent filaments of the discharge lamps to be preheated in a targeted fashion by means of a transformer with four windings.

In one advantageous refinement of the inventive device, the supply branch comprises a resonance inductor and a resonance capacitor. The two lamps can thereby be operated with the aid of one resonant circuit. The resonance inductor can be used as an inductor. Furthermore, the resonance inductor can be at least a

part of a coupling-out transformer for supplying the coupling-out device, or have an appropriate tap therefor.

5 The current control device advantageously comprises a PTC thermistor with a positive temperature coefficient. This component permits a relatively simple and cost-effective control of the preheating for the lamps. Instead of the PTC thermistor, the current control
10 device can comprise a transistor. It is possible thereby to control the preheating in a more targeted but also more complicated way.

A sequential starting capacitor can be provided in
15 parallel with the first and/or second contact device; it can be used advantageously to control the sequential starting sequence in the case of at least two lamps. Consequently, it is possible to achieve sequential starting in order to avoid very high ignition
20 currents/voltages being reached, said starting permitting the use of components which cannot be so highly loaded and are therefore more cost-effective.

The inventive device is advantageously integrated in an
25 electronic ballast for fluorescent lamps. It is thereby possible to operate two or more lamps with the aid of one ballast.

Brief description of the drawings

30

The invention will now be explained in more detail with the aid of the attached drawings, in which:

figure 1 shows a circuit diagram of a half
35 bridge with a load circuit in accordance with the prior art, for operating a fluorescent lamp;

figures 2a, 2b, show variants of the load circuits in
2c accordance with the prior art; and

5 figure 3 shows variants of inventive load
circuits for operating at least two
lamps.

Detailed description of the invention

10

The exemplary embodiments described below constitute
only preferred embodiments of the present invention.

Figure 3a shows an inventive load circuit in a ballast
15 for two discharge lamps 71 and 72. The discharge lamp
71 has two incandescent filaments 711 and 712.
Likewise, the second discharge lamp 72 has incandescent
filaments 721 and 722. The circuit has terminals 20 and
21 for the incandescent filament 711 of the first
20 discharge lamp 71, terminals 22 and 23 for the second
incandescent filament 712 of the first discharge lamp
71, terminals 24 and 25 for the first incandescent
filament 721 of the second discharge lamp 72, and
terminals 26 and 27 for the second incandescent
25 filament 722 of the second discharge lamp 72.

The supply branch for the two discharge lamps 71 and 72
comprises a resonant circuit composed of a resonance
capacitor C_{res} and a resonance inductor L_{res} . The
30 resonance capacitor C_{res} is connected between the
terminals 20 and 26.

The coupling-out circuit 30 is driven via a coupling-
out transformer that comprises, on the primary side,
35 the inductor or resonance inductor L_{res} and, on the
secondary side, a coil L_a . In addition to the secondary
coil L_a of the coupling-out transformer, this coupling-

out circuit 30 comprises a temperature-dependent thermistor PTC and a primary coil L_{hp} of a heating transformer. The heating transformer has three coils on the secondary side. The first secondary-side heating
5 coil L_{hs1} is connected between the terminals 20 and 21 for the first incandescent filament 711 of the first discharge lamp 71. The second secondary coil L_{hs2} is connected to the terminals 23 and 25 for the second incandescent filament 712 of the first discharge lamp
10 and the first incandescent filament 721 of the second discharge lamp 72. The third secondary heating coil L_{hs3} is connected between the terminals 26 and 27 for the second incandescent filament 722 of the second discharge lamp 72.

15 Moreover, the terminals 22 and 24 for the two incandescent filaments 712 and 721 are interconnected. Finally, a sequential starting capacitor C_{seq} is connected between the terminals 24 and 26.

20 The mode of operation of the load circuit illustrated in figure 3a may be explained in more detail below. The supply branch with the resonant circuit C_{res} and L_{res} is very strongly damped at the beginning of operation. The
25 reason for this is that at the start of operation the temperature-dependent thermistor PTC is still cool and therefore of low resistance. Consequently, a high energy component can be coupled out from the supply branch into the coupling-out circuit 30 via the
30 coupling-out transformer L_{res} , L_a . The heating current flowing in the coupling-out circuit 30 is transmitted to the respective incandescent filaments via the heating transformer with the primary-side winding L_{hp} and the three secondary-side windings L_{hs1} , L_{hs2} and L_{hs3} .
35 In this case, the incandescent filaments 711 and 722 are respectively supplied individually by means of the coils L_{hs1} and L_{hs3} , and the two incandescent filaments

712 and 721 are supplied jointly by means of the coil L_{hs2} .

5 The two lamps 71 and 72 constitute a voltage divider at the resonance capacitor C_{res} . By virtue of the fact that the sequential starting capacitor C_{seq} is connected in parallel with the second discharge lamp 72, a smaller voltage drops across the second discharge lamp 72 than across the first discharge lamp 71. Consequently, the
10 first discharge lamp 71 ignites before the second discharge lamp 72.

At the end of the heating phase, the temperature-dependent thermistor PTC itself has been heated to such
15 an extent that it has become of high resistance. Consequently, the damping of the resonant circuit C_{Res} , L_{Res} decreases, and the voltage across the discharge lamps 71 and 72 rises on the basis of the rise in the quality of the resonant circuit.

20 After the ignition, the current flows to the terminal 26 in the burning phase substantially from the terminal 20 via the incandescent filament 711, the incandescent filament 712, the terminal 22, the terminal 24, the
25 incandescent filament 721 and the incandescent filament 722.

Owing to the high resistance of the thermistor PTC, the current in the coupling-out circuit 30, thus also the
30 heating current for the incandescent filaments is greatly reduced in the burning phase. Consequently, all the filaments are subjected only to minimal heating during operation of the lamp in the burning phase.

35 A second embodiment of the present invention is illustrated in figure 3b. It differs from the first embodiment in accordance with figure 3a only in that

the resonance inductor is bipartite. It comprises the portions L_{res1} and L_{res2} , the second part L_{res2} constituting the primary coil of the coupling-out transformer. Owing to the bipartite nature of the
5 resonance inductor, it is possible to use a standard transformer for coupling out, and to adapt the primary coil L_{res2} thereof to the resonance requirements of the supply branch by means of a separate inductor L_{res1} .

10 A further embodiment of the present invention is illustrated in figure 3c. Once again, the circuit design is virtually identical to that of figure 3a. Instead of a coupling-out transformer, however, use is made here of a tap at the resonance inductor L_{res} . This
15 means that the coupling-out circuit 30 is directly coupled to the resonance inductor L_{res} . The resonant circuit 30 therefore comprises the tapped part of the resonance inductor L_{res} in series with the PTC thermistor and the primary coil L_{hp} of the heating
20 transformer.

The modes of operation of the embodiments illustrated in figures 3b and 3c are essentially identical to that of figure 3a. The coupling-out circuit is driven by
25 direct or inductive coupling to provide the heating current.